Your Gateway Plasma TV

user's guide



Setting up | Troubleshooting | Gateway

Contents

1 Introducing Your Gateway Plasma TV 1

Features 2
Important Safeguards 3
Package contents 5
Turning on the main power 8
Front panel controls 11
Back panel connections 13
Audio and video connections 14
RGB and DVI connections 15

2 Connecting Components 17

Understanding video connections 18
Connecting your DVD player 19
Using component video 19
Using S-Video 20
Using composite video 21
Connecting your HDTV set-top box 22
Using component video 22
Using RGB video 23
Connecting your VCR or video camera 24
Using S-Video 24
Using composite video 25
Using coaxial (RF) 26
Connecting off-air TV or cable TV 27
Connecting external amplified speakers 28
Connecting an external receiver or amplifier 29
Connecting a subwoofer 30
Connecting a computer 31
Using DVI video 31
Using RGB video 32
Connecting an external monitor 33

3 Adjusting Your Plasma TV Settings 35

Using the OSD 36
OSD menus and options 37

4 Maintenance and Troubleshooting 45

Cleaning and maintenance 46

Cleaning the screen 46
Cleaning the exterior 46
Avoiding image burn-in 47
Troubleshooting 47
Telephone support 49

A Signal Frequency Information 51

TV, AV1, and AV2 inputs 52
Component 1 and Component 2 inputs 52
RGB and DVI inputs 53

B Safety, Regulatory, and Legal Information. 55

Index 61



1 Introducing Your Gateway Plasma TV

This chapter provides basic information about your Gateway Plasma TV.

Read this chapter to learn about:

- Features
- Warnings and safeguards
- Package contents
- Controls and connections



Features

Your plasma TV features:

- A bright, flicker-free image
- Automatic detection and conversion of film content for correct display with minimal motion artifacts (noise)
- Accurate color processing
- Two high-definition component video input sources that automatically synchronize the display to match the incoming source
- Picture-in-picture (PIP) and picture-on-picture (POP) modes that let you watch two programs simultaneously
- HDTV signal compatibility using an external HDTV decoder with RGB or component video outputs
- Digital zoom modes get rid of “black bars” around the display image
- A built-in BBE® sound processor that maximizes the sound quality
- A built-in SRS® sound processor that simulates “surround” effects using only two speakers.
- Selectable fixed/variable audio outputs
- Built-in internal amplifier and speakers
- Connections for adding a separate, powered subwoofer
- A built-in Digital Visual Interface (DVI) to eliminate the need for digital-to-analog conversion
- 1280 × 1024 SXGA support for computer input.
- 720p and 1080i support for HDTV signals

Important Safeguards

Warning

Risk of electric shock - Do not open

To reduce the risk of electric shock, do no remove the back cover. There are no user-serviceable parts inside. Removing the back cover voids the warranty.

Have your plasma TV repaired by qualified service personnel only.

Warnings and precautions

- Do not place your hands, face, or objects close to the ventilation openings of your plasma TV. The top of your plasma TV gets very hot from exhaust air that is released through the ventilation openings. Burns or personal injuries may occur if you are too close to the plasma TV. Damage may occur if you place any object near the top of your plasma TV.
- Disconnect all cables before moving your plasma TV. Moving your plasma TV with its cables attached may damage the cables and cause fire or electric shock danger.
- Do not expose your plasma TV to rain or moisture.
- Keep your plasma TV away from excessive dust, high temperatures, moisture, or direct sunlight.
- Use your plasma TV in a well-ventilated area and do not cover the ventilation openings.
- Do not modify your plasma TV or use an unshielded power cord or video input source cable, or you may experience excessive interference.
- Disconnect your plasma TV and unplug the power cord when not used for a long period of time.
- If the picture displayed is in any way abnormal, turn off your plasma TV, then disconnect it from the electrical outlet. Make sure that your video input source cable is connected correctly, then reconnect your plasma TV to the electrical outlet.
- Disconnect your plasma TV from the electrical outlet before cleaning or performing maintenance. Do not use liquid or aerosol cleaners. Use only a slightly damp cloth for cleaning.
- Do not place your plasma TV on an unstable cart, stand, or table. Your plasma TV may fall, causing serious damage.

- Do not place your plasma TV on a bed, sofa, rug, or other similar surfaces.
- Never place your plasma TV near or over a radiator or heat source.
- Do not install your plasma TV in an enclosed area unless correct ventilation is provided.
- Your plasma TV should be operated from the type of power source indicated on the label. If the type of available power is unknown, consult your electrician or local power company.
- Your plasma TV is equipped with a 3-pin grounded plug. The plug will only fit into a grounded power outlet. This is a safety feature. If you cannot plug the power cord into the outlet, contact your electrician. Do not alter the plug because this will defeat the safety feature.
- Do not rest objects on the power cord and avoid placing the power cord near high traffic areas.
- Do not overload wall outlets and extension cords because this can result in a risk of fire or electric shock.
- Unplug your plasma TV and contact qualified service personnel if:
  - The power cord or plug is damaged or frayed.
  - Liquid has been spilled into your plasma TV.
  - Your plasma TV has been exposed to water or moisture.
  - Your plasma TV does not operate normally when the operating instructions are followed. Adjust only those controls that are covered by the operating instructions. Incorrect adjustment of other controls may result in damage which often requires extensive work by a qualified technician to restore your plasma TV to normal operation.
  - Your plasma TV has been dropped or the cabinet has been damaged.

Avoid image burn-in

- Displaying the same stationary images over an extended period of time, such as a black bar, stock ticker, video game, or a shopping channel logo, can leave a permanent ghost image (burn-in). Avoid burn-in by mixing your viewing patterns. Do not show the same stationary image for more than 15% of your total viewing time in any one week.
- Your warranty does **NOT** cover screen burn-in.

Package contents

Along with your plasma TV, the packaging box contains the following items:

Remote control

- OR -

Two AA batteries

Power cord

User guide	
Remote control user guide	

You can purchase these optional accessories for your plasma TV:

- **Wall mount kit.** The wall mount kit contains all of the required hardware for mounting your plasma TV on your wall. (Gateway recommends you use a qualified installer.) For more information, see the Wall Mount Installation Guide at support.gateway.com.
- **Cable kits**. Gateway cable kits consist of high-quality gold cables of various lengths, including:
  - DVI-D video cable
  - RCA audio cable
  - RCA component video cable
  - RCA composite video cable
  - S-Video cable
  - VGA video cable

Contact Gateway for these and other accessories.

Turning on the main power

To turn on the main power:

1 Connect the power cord to the power cord connector on the back of your plasma TV, then plug the other end of the power cord into a correctly grounded electrical outlet or surge protector.



- OR -



2 Press the **MAIN POWER** switch. The status LED on the front turns yellow and your plasma TV is ready to turn on.



- OR -



3 Press the **POWER** button on the front of your plasma TV. The Status LED on the front turns green.

Warning

If you will be away for an extended period of time, turn off your plasma TV with the MAIN POWER switch instead of using the remote control or front POWER button.

For added protection during a lightning storm or when it is left unattended or unused for long periods of time, unplug your plasma TV from the wall outlet and disconnect the antenna or cable system.

Front panel controls



Button	Description
Volume and Adjustment +/–	Increases or decreases the volume. OSD active: Adjusts on-screen display (OSD) options. For more information, see “Using the OSD” on page 36.
Menu +/–	Opens and closes the OSD. OSD active: Selects on-screen display (OSD) options. For more information, see “Using the OSD” on page 36.
Input	Switches between available input sources.
Remote control sensor	Receives signals from the remote control. Do not block.
Status LED	▪ Not lit - No AC power detected. The MAIN POWER switch is off or the power cord is not connected. ▪ Solid Yellow - The MAIN POWER switch is on and your plasma TV is off. ▪ Solid Green - Your plasma TV is on.
Power	Turns your plasma TV on and off after the MAIN POWER switch is turned on. When you turn your plasma TV on or off, wait three seconds before pressing this button again.

Back panel connections



Connector	Description
Audio and video connections	See “Audio and video connections” on page 14.
RGB and DVI connections	See “RGB and DVI connections” on page 15.

Audio and video connections



Connector	Description
Antenna	Connects to a VHF/UHF antenna or cable TV.
DVI Audio In	Connects to the audio on a DVI device, such as a computer or set-top box.
Video 1/Audio In	Connects to a composite audio/video device, such as a VCR.
Component Video 1/ Audio In	Connects to a component audio/video device, such as a DVD player.
Audio Out	Connects to an audio device, such as a receiver.
External Speaker Switch	Connects to the speaker switch jack on switchable external speakers or an external receiver or amplifier.
Subwoofer	Connects to an external subwoofer.
RGB Audio In	Connects to the audio on an RGB device, such as a computer or set-top box.
S-Video/Audio In	Connects to an S-Video device, such as a satellite dish receiver or digital cable box.
Component Video 2/ Audio In	Connects to a component video device, such as an HDTV set-top box.

RGB and DVI connections



Connector	Description
RGB In	Connects to an RGB video device, such as a computer or set-top box.
RGB Out	Connects to an external RGB monitor.
DVI In	Connects to a DVI video device, such as a computer or set-top box.
RS-232	Connects to a computer to display the computer image on the plasma TV or monitor using customized software (typically used by business, education, or government). For more information see the *RS-232 Serial Connection Technical Reference* at support.gateway.com.



Connecting Components 2

Read this chapter to learn how to connect:

- DVD players
- HDTV decoder set-top boxes
- VCRs
- Off-air TV and cable TV
- External audio devices
- Computers

Warning

Before connecting any external components, unplug your plasma TV. To restart your plasma TV, see “Turning on the main power” on page 8.



Understanding video connections

Your plasma TV has four types of standard video connections. You should use the best connection available to get the best display. For example, if your DVD player supports a component video connection, connect the DVD player to your plasma TV using component video instead of composite video or S-Video.

Connection Quality	Cable and Connector	Description
Basic		**Coaxial (RF).** The video and audio signals are both carried in one cable (the other three connection types only handle video, and require separate connections for sound). Coaxial is the only way to connect an antenna to your plasma TV.
Good		**Composite**. The video signal is carried through a single “pin.” This connection method is the one that is most commonly found on devices.
Better		**S-Video.** The video signal is split into two signals, black-and-white and color. Text displayed on-screen through this connection will be noticeably sharper then composite or coaxial (RF).
Best		**Component.** The video signal is split into three signals, two color, and one black-and-white. Use component video to take advantage of the superior picture provided by signal sources as HDTV and *progressive* DVD.

Connecting your DVD player

Using component video

To connect your DVD player using component video:



1. Connect the green-colored Y jack on the back of your DVD player to the green-colored Y1 jack on the back of your plasma TV.
2. Connect the red-colored P_R or C_R jack on the back of your DVD player to the red-colored P_R1/C_R1 jack on the back of your plasma TV.
3. Connect the blue-colored P_B or C_B jack on the back of your DVD player to the blue-colored P_B1/C_B1 jack on the back of your plasma TV.
4. Connect the red (R) and white (L) audio jacks on the back of your DVD player to the R and L audio-in jacks on the back of your plasma TV.
5. Select **COMPONENT1** using the **INPUT** button on the front of your plasma TV.

Using S-Video

To connect your DVD player using S-Video:



1. Connect the S-Video jack on the back of your DVD player to the S-VIDEO jack on the back of your plasma TV.
2. Connect the red (R) and white (L) audio jacks on the back of your DVD player to the R and L audio-in jacks on the back of your plasma TV.
3. Select **AV2 (S)** using the **INPUT** button on the front of your plasma TV.

Using composite video

To connect your DVD player using composite video:



1. Connect the yellow video jack on the back of your DVD player to the yellow VIDEO 1 jack on the back of your plasma TV.
2. Connect the red (R) and white (L) audio jacks on the back of your DVD player to the R and L audio-in jacks on the back of your plasma TV.
3. Select **AV1** using the **INPUT** button on the front of your plasma TV.

Connecting your HDTV set-top box

Using component video

To connect your HDTV decoder set-top box using component video:



1. Connect the green Y jack on the back of your HDTV set-top box to the green Y2 jack on the back of your plasma TV.
2. Connect the red P_R or C_R jack on the back of your HDTV set-top box to the red P_R2/C_R2 jack on the back of your plasma TV.
3. Connect the blue P_B or C_B jack on the back of your HDTV set-top box to the blue P_B2/C_B2 jack on the back of your plasma TV.
4. Connect the red (R) and white (L) audio jacks on the back of your HDTV set-top box to the R and L audio-in jacks on the back of your plasma TV.
5. Select **COMPONENT1** using the **INPUT** button on the front of your plasma TV.

Using RGB video

To connect your HDTV decoder set-top box using RGB video:



1. Connect the 15-pin D-Sub RGB jack on the back of your HDTV set-top box to the RGB-IN jack on the back of your plasma TV.
2. Connect the red (R) and white (L) audio-out jacks on the back of your HDTV set-top box to the R and L audio-in jacks on the back of your plasma TV.
3. Select **RGB** using the **INPUT** button on the front of your plasma TV.

After you connect your HDTV set-top box to the RGB input jack on your plasma TV, you may need to adjust various plasma TV picture settings to correctly match the output from the HDTV set-top box (see “PICTURE – RGB/DVI video sources” on page 38).

Connecting your VCR or video camera

Using S-Video

To connect your VCR or video camera using S-Video:



1. Connect the S-Video jack on the back of your VCR or video camera to the S-VIDEO jack on the back of your plasma TV.
2. Connect the red (R) and white (L) audio jacks on the back of your VCR or video camera to the R and L audio-in jacks on the back of your plasma TV.
3. Select **AV2 (S)** using the **INPUT** button on the front of your plasma TV.

Using composite video

To connect your VCR or video camera using composite video:



1. Connect the yellow video jack on the back of your VCR or video camera to the yellow VIDEO 1 jack on the back of your plasma TV.
2. Connect the red (R) and white (L) audio jacks on the back of your VCR or video camera to the R and L audio-in jacks on the back of your plasma TV.
3. Select **AV1** using the **INPUT** button on the front of your plasma TV.

Using coaxial (RF)

To connect your VCR using coaxial (RF) audio and video:



1. Connect the “output to TV” (RF out or Antenna out) jack on the back of your VCR to the ANT jack on the back of your plasma TV.
2. Select **TV** using the **INPUT** button on the front of your plasma TV.

If you have an off-air antenna or cable box, connect your off-air antenna or cable TV cable to the ANT connector on the back of your VCR.

Warning

If an outdoor antenna or cable system is connected to your plasma TV, make sure that the antenna or cable system is correctly grounded. For more information, see “Television antenna connectors protection (for systems fitted with TV/cable TV tuner cards)” on page 57.

Connecting off-air TV or cable TV

To connect off-air TV or cable TV using coaxial (RF) audio and video:



1. Connect the coaxial (RF) connector from your antenna or cable box to the ANT connector on the back of your plasma TV.
2. Select **TV** using the **INPUT** button on the front of your plasma TV.

If you have connected a VCR to the ANT connector on the back of your plasma TV, connect your off-air TV or cable TV cable to the ANT connector on the back of your VCR.

Warning

If an outdoor antenna or cable system is connected to your plasma TV, make sure that the antenna or cable system is correctly grounded. For more information, see “Television antenna connectors protection (for systems fitted with TV/cable TV tuner cards)” on page 57.

Connecting external amplified speakers

You can connect your plasma TV to a set of external, amplified speakers using the AUDIO OUT jacks located on the back of your plasma TV. If your speakers have remote turn-on/off capability, connect the external speaker switch.

To connect your external amplified speakers:



1. Connect the red (R) and white (L) audio jacks on the back of your speakers to the AUDIO OUT jacks on the back of your plasma TV.
2. If your external amplified speakers accept remote turn-on/off signals, connect the external speaker switch. Not all external amplified speakers can accept remote turn-on/off signals.

Connecting an external receiver or amplifier

You can connect an external receiver or amplifier to your plasma TV. Your plasma TV is equipped with a external speaker switch that can automatically send a remote turn-on/off signal to an external receiver or amplifier.

To connect your external receiver or amplifier:



1. Connect the red (R) and white (L) audio jacks on the back of your external amplifier or receiver to the AUDIO OUT jacks on the back of your plasma TV.
2. If your external amplifier or receiver accepts remote turn-on/off signals, connect the external speaker switch. Not all external amplifiers or receivers can accept remote turn-on/off signals.

Connecting a subwoofer

Your plasma TV has built-in speakers. You can enhance the bass response of your plasma TV's sound by connecting an external, amplified subwoofer.

To connect your subwoofer:



1. Connect the audio jack on the back of your subwoofer to the SUBWOOFER jack on the back of your plasma TV.
2. If your subwoofer accepts remote turn-on/off signals, connect the external speaker switch. Not all subwoofers can accept remote turn-on/off signals.

Connecting a computer

Using DVI video

To connect your computer using DVI video:



1. Connect the DVI connector on your computer to the DVI-In connector on the back of your plasma TV.
2. Connect the Audio Out jack on your computer to the DVI Audio In jacks on the back of your plasma TV.
3. Select **DVI** using the **INPUT** button on the front of your plasma TV.

Using RGB video

To connect your computer using RGB video:



1. Connect the 15-pin D-Sub RGB connector on your computer to the RGB-IN connector on the back of your plasma TV.
2. Connect the Audio Out jack on your computer to the RGB Audio In jacks on the back of your plasma TV.
3. Select **RGB** using the **INPUT** button on the front of your plasma TV.

Connecting an external monitor

A RGB loop-out (labeled RGB Out) lets you connect another RGB monitor. The RGB loop-out displays the same signal as the RGB In video input source.

To connect your external monitor:



- Connect the RGB connector on your monitor to the RGB Out connector on the back of your plasma TV.

The maximum physical display resolution of the external monitor is 640 × 480 when the aspect ratio is set to 4:3, and 852 × 480 when the ratio is set to 16:9. If the computer's display resolution exceeds these maximums, the external monitor eliminates the extra dots which results in a loss of detail and picture clarity.



Adjusting Your Plasma TV Settings

3

Read this chapter to learn how to adjust your plasma TV settings from the on-screen display (OSD).

You can also use your remote control to change some settings. For more information, see *Your Gateway Remote Control User's Guide*.



Using the OSD

Your plasma TV features an on-screen display (OSD) that lets you adjust and save contrast, brightness, and other settings. The TV saves changes you make to the settings, even if you turn off the TV.

To adjust settings from the OSD:

1. Press the MENU + or – button on the front of your plasma TV. The OSD opens.
2. Press the ADJ + or – button on the front of your plasma TV to select the menu you want.
3. Press the MENU + or – button on the front of your plasma TV to select a menu option.
4. Press the ADJ + or – button on the front of your plasma TV to adjust the option setting.
5. Press the MENU + or – button on the front of your plasma TV. The OSD closes.

OSD menus and options

You can use these OSD menus and options to adjust various settings for your plasma TV.

OSD Menu	Description
PICTURE – TV, AV1, AV2, Component 1, and Component 2 video sources 	**INPUT SOURCE.** Switches between available video input sources. **CONTRAST.** Adjusts the contrast of the picture. **BRIGHT.** Adjusts the brightness of the picture. You may need to readjust brightness after the plasma TV warms up. **COLOR.** Adjusts the color saturation making colors more intense. **TINT.** Adjusts the color of flesh tones. **SHARPNESS.** Adjust the amount of detail enhancement. **COLOR TEMPERATURE.** Adjusts the white balance. **CLOCK PHASE.** Adjusts your plasma TV to match the video input source. **SCREEN WIDTH.** Adjusts the screen width to 4:3, 16:9, or PANORAMA viewing mode. **ZOOM.** Moves or stretches the display image when the screen width is set to 16:9. Zoom1 moves the image upward (good for presentations with sub-titles). Zoom2 stretches 1.85:1 content to fill the screen. Zoom3 stretches 2.35:1 content to fill the screen. **GEOMETRIC ADJUST**. Controls the V-SIZE, V-CENTER, H-WIDTH, and H-POSITION of the display image. Only available in Component 1 and Component 2 mode.

OSD Menu	Description
PICTURE – RGB/DVI video sources 	**INPUT SOURCE.** Switches between available video input sources. **CONTRAST.** Adjusts the contrast of the picture. **BRIGHTNESS.** Adjusts the brightness of the picture. You may need to readjust brightness after the plasma TV warms up. **COLOR TEMPERATURE.** Adjusts the white balance. **CLOCK PHASE.** Adjusts your plasma TV to match the video input source. **SCREEN WIDTH.** Adjusts the screen width to 4:3 or 16:9 viewing mode. **V-SIZE.** Adjusts the vertical screen size. **V-CENTER.** Adjusts the vertical screen position. **H-WIDTH.** Adjusts the horizontal screen size. **H-POSITION.** Adjusts the horizontal screen position.

OSD Menu	Description
SOUND  	**BASS.** Adjusts the bass. The AUDIO OUTPUT option must be set to VARIABLE to adjust this setting. **TREBLE.** Adjusts the treble. The AUDIO OUTPUT option must be set to VARIABLE to use this option. **BALANCE.** Adjusts the balance level between the channels. The AUDIO OUTPUT option must be set to VARIABLE to adjust this setting. **SURROUND.** Switches between STEREO, MONO, or turns surround OFF. The AUDIO OUTPUT option must be set to VARIABLE to use this option. **BBE.** Turns the BBE option on or off. Turn this option on when you are listening to live-performance programs. The AUDIO OUTPUT option must be set to VARIABLE to use this option. **BASS EXTENSION.** Extends the level of BASS sent to the audio out jack. The AUDIO OUTPUT option must be set to VARIABLE and the INNER SPKR option must be turned off to use this option. **VOLUME.** Adjusts the volume. The AUDIO OUTPUT option must be set to VARIABLE to use this option. **INNER SPKR.** Turns the built-in speakers on or off. The AUDIO OUTPUT option must be set to VARIABLE to use this option. **AUDIO OUTPUT.** Changes the audio output options for the plasma TV. FIXED bypasses your plasma TV's internal sound controls. VARIABLE lets you adjust the type of output your plasma TV sends to the built-in speakers or the audio output jack.

OSD Menu	Description
PIP/POP  	**PIP.** Turns PIP mode on or off. When PIP is turned on, you can display two pictures at one time. One picture is displayed on the full screen and the other picture is displayed in a small window. The picture on the full screen is the main picture. The picture in the window is the sub-picture. You can use PIP mode if your video input source is set to TV, AV, S-Video, Component 1, or Component 2 and the video input source is 480i or lower (such as a non-progressive DVD player). PIP mode does not work with component video input sources higher than 480i (such as an HDTV set-top box or progressive DVD player), RGB, or DVI video sources. **SOURCE.** Changes the video input source of the sub-picture when PIP is turned on. **POSITION.** Moves the sub-picture within the screen. FIXED lets you use the H-LOCATOR and V-LOCATOR options to place the sub-picture in one of the four corners of the screen. VARIABLE lets you use the H-LOCATOR and V-LOCATOR options to move the sub-picture anywhere within the screen. **H-LOCATION.** Moves the sub-picture left or right. **V-LOCATION.** Moves the sub-picture up or down. **SWAP.** Swaps the picture and the sub-picture.

OSD Menu	Description
PIP/POP (continued)	**POP.** Turns POP mode on or off. When POP is turned on, the screen is split into two pictures. The picture on the left side of your screen is the main picture. The picture on the right side of the screen is the sub-picture. You can use POP mode if your video input source is set to TV, AV, S-Video, Component 1, or Component 2 and the video input source is 480i or lower (such as a non-progressive DVD player). POP mode does not work with component video input sources higher than 480i (such as an HDTV set-top box or progressive DVD player), RGB, or DVI video sources. **SOURCE.** Changes the video input source of the sub-picture when POP is turned on. **SCREEN RATE.** Changes the aspect ratio of the sub-picture. **SWAP.** Swaps the main picture and the sub-picture.

OSD Menu	Description
TV  	**CHANNEL.** Changes the TV channel. **CHANNEL STATUS.** Sets the status of the TV channel. NORMAL is the default. FAV programs the channel as a favorite channel. LOCK prevents the channel from being viewed. You need the remote control to use this option. For more information, see *Your Gateway Remote Control User's Guide*. ERASE removes the channel from the channel list. **MTS.** Changes the sound output for TV programs. Switch between STEREO, MONO, or SAP (Second Audio Program) for audio simulcasts. The TV program must support the output option. **CCD.** Activates closed captioning. **V-CHIP.** Activates the Parental Guide. You need the remote control to use this option. For more information, see *Your Gateway Remote Control User's Guide*. **SET PARENTAL CODE.** Sets a password for the Parental Guide. You need the remote control to use this option. For more information, see *Your Gateway Remote Control User's Guide*. **SET RATING.** Blocks individual programs based on program ratings. You need the remote control to use this option. For more information, see *Your Gateway Remote Control User's Guide*. **CH SEARCH.** When this option is turned on, your plasma TV only displays channels that have a signal when you change channels. **TUNER SOURCE.** Sets the source for the tuner. CABLE sets the tuner for cable or a satellite dish. AIR sets the tuner for an antenna. **BACKGROUND.** Displays a background color when a video signal is not available. **BACKGROUND COLOR.** Changes the color of the background when the BACKGROUND option is turned on.

OSD Menu	Description
OTHER  	**OSD TIMEOUT.** Turns the OSD timer on and off. **To avoid image burn-in, we recommend that you keep this timer turned on.** **SET OSD TIME.** Specifies the number of seconds the OSD menu is displayed before it turns off automatically. The OSD TIMEOUT option must be turned on to use this option. **OSD BRIGHTNESS.** Adjusts the brightness level of the OSD menu. **OSD BACKGROUND.** Switches the OSD menu background to blue or transparent. **OSD LANGUAGE.** Changes the language of the OSD menu. **SLEEP.** Turns the sleep timer on and off. **SLEEP TIME.** Adjusts the number of minutes the plasma TV waits before it automatically turns off. You can specify from 1 to 120 minutes. The SLEEP option must be turned on. **POWER SAVE.** Turns power save mode on or off. The plasma TV goes into sleep mode with RGB and DVI video input. For more information, see the documentation that came with your computer. **POWER ON SEQUENCE.** Selects the power-on sequences. 1 STEP. Turns the plasma TV on or off using the MAIN POWER switch. 2 STEP (factory default). Press the MAIN POWER switch to activate the plasma TV. This puts the plasma TV in suspend mode. Then use the POWER button on the front of the plasma TV to turn it on and off. For more information, see “Turning on the main power” on page 9. **RESET**. Resets picture settings to the factory default. **S/W VERSION.** Shows the version of the software your plasma TV is using.



Maintenance and Troubleshooting

4

Read this chapter to learn how to maintain and troubleshoot your plasma TV.



Cleaning and maintenance

Cleaning the screen

- Do not use substances such as glass cleaners, solvents, and thinners.
- The screen of your plasma TV has been specially treated. Wipe the surface gently using only a cleaning cloth or a soft, lint-free cloth.
- If the surface is particular dirty, use a soft cloth and water to clean the screen. Squirt a little water on the cloth (never directly on the screen), then wipe the screen with the cloth.

Warning

The screen of your plasma TV is made of specially coated glass and can be scratched or damaged by abrasive or ammonia-based window cleaners.

Scratches on the bezel or glass are not covered by your warranty.

- Do not scratch or hit the surface of the screen with your fingers or any hard objects.

Cleaning the exterior

- Your plasma TV is cooled by air circulated through the vents on the case, so keep the vents free of dust. With your plasma TV turned off and unplugged, brush the dust away from the vents with a damp cloth. Be careful not to drip any water into the vents. Do not attempt to clean dust from the inside of your plasma TV.
- Do not use abrasive or solvent cleaners because they can damage the finish on components.
- Do not allow any excessive water or moisture to come into contact with the surface of your plasma TV. If water or moisture gets inside your plasma TV, operating problems and electrical and shock hazards may result.
- Do not scratch or hit the cabinet with your fingers or any hard objects.
- Do not place articles made from rubber or PVC near the cabinet for any extended periods of time.

Avoiding image burn-in

- Displaying the same stationary images over an extended period of time, such as a black bar, stock ticker, video game, or a shopping channel logo, can leave a permanent ghost image (burn-in). Avoid burn-in by mixing your viewing patterns. Do not show the same stationary image for more than 15% of your total viewing time in any one week.
- Your warranty does **NOT** cover screen burn-in.

Troubleshooting

Use the following information to solve common problems.

You cannot see a picture

- Make sure that the power cord is plugged into a grounded electrical outlet.
- Make sure that the main power switch and power button are turned on.
- Make sure that the selected input source is connected to a working input source.
- If your plasma TV is connected to your computer in RGB mode, press any key on your keyboard to “wake” your computer.

You see a distorted picture or hear unusual sound

- You may be getting interference from electrical appliances, cars, motorcycles, or fluorescent lights. Try moving your plasma TV to another location.

The color is abnormal

- Make sure that the input source cable is connected securely and correctly to the back of your plasma TV.

The picture has abnormal patterns

- Make sure that the input source cable is attached securely and correctly to the back of your plasma TV.
- Make sure that the video input source is within the range of your plasma TV. Compare the video input source’s specifications with your plasma TV specifications.

The display image does not cover the entire screen

- If you are using RGB mode, make sure that H-WIDTH and V-SIZE in the OSD are set correctly.
- If you are using TV, AV1, AV2, or component with 480i input, use the SCREEN WIDTH or WIDE button on the remote control to scroll through various screen modes.

You can see a picture but you cannot hear sound

- Make sure that the volume is not turned down.
- Make sure that the sound is not muted.
- Make sure that your audio input source cables are connected securely and correctly.

The monitor has pixels that are always dark

- Your plasma TV is manufactured using an extremely high level of precision technology. However, sometimes some pixels of your plasma TV may not display. Pixel defects within industry specifications are inherent to this type of product and do not constitute a defective product.

An image remains on the screen even after you turn off your plasma TV

- A still image may have been displayed for an extended period of time causing burn-in. For more information about burn-in, see page 43.

You see “noise” or “trash” on the screen

- When your plasma TV’s digital capabilities exceed a digital broadcast signal, the signal is up-converted (increased) to match your plasma TV’s display capabilities. Up-converting can cause noise or trash.

Screen brightness is diminished

- Video display devices experience degradation of brightness over the life of the device. Normal brightness degradation is not covered by your warranty.

Telephone support

If this troubleshooting information does not resolve your problem or if you have other questions relating to your plasma TV, call our Service Center at 888-737-MyGW (6949).

For more information about Gateway, visit www.gateway.com.



Signal Frequency Information

A

Read this appendix for signal frequency information.



TV, AV1, and AV2 inputs

Horizontal (KHz)	Vertical (Hz)	Format
15.7	60	NTSC Video
15.6	50	PAL Video

Component 1 and Component 2 inputs

Horizontal (KHz)	Vertical (Hz)	Format
15.7	60	NTSC Video
15.6	50	PAL Video
15.7	60	480i (SDTV)
31.5	60	480p (EDTV)
33.0	60	1080i (HDTV)
45.0	60	720p (HDTV)

RGB and DVI inputs

Mode	Horizontal (KHz)	Vertical (Hz)	Format	Refresh
1	31.5	59.9	640 × 480 (VGA)	60
2	37.9	72.8	640 × 480 (VGA)	72
3	37.5	75.0	640 × 480 (VGA)	75
4	43.3	85.0	640 × 480 (VGA)	85
5	35.1	56.3	800 × 600 (SVGA)	56
6	37.9	60.3	800 × 600 (SVGA)	60
7	48.1	72.2	800 × 600 (SVGA)	72
8	46.9	75.0	800 × 600 (SVGA)	75
9	53.7	85.0	800 × 600 (SVGA)	85
10	48.4	60.0	1024 × 768 (XGA)	60
11	56.5	70.0	1024 × 768 (XGA)	70
12	60.0	75.0	1024 × 768 (XGA)	75
13	68.7	85.0	1024 × 768 (XGA)	85
14	64.0	60.0	1280 × 1024 (SXGA)	60

Mode	Horizontal (KHz)	Vertical (Hz)	Format	Refresh
15*	80.0	75.0	1280 × 1024 (SXGA)	75
16*	91.1	85.0	1280 × 1024 (SXGA)	85
18	31.5	70.0	720 × 400 (DOS)	70
19	31.5	50.0	640 × 480 (VGA)	50
20*	45.0	60.0	1266 × 720p (HDTV)	60
21*	33.8	60	1920 × 1080i (HDTV)	60i
22	31.5	70.0	640 × 350 (VGA)	70
23	31.4	60.0	852 × 480 (WVGA)	60
24	35.0	66.7	640 × 480 (Apple)	67
25	49.7	74.6	832 × 624 (Apple)	75
26	68.7	75.0	1152 × 870 (Apple)	75

* These modes not available in RGB mode with DVI output.



Safety, Regulatory, and Legal Information

B

Regulatory compliance statements

United States of America

Federal Communications Commission (FCC)
Unintentional emitter per FCC Part 15

This device has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.





This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio or television reception. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause interference to radio and television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna
- Increase the separation between the equipment and receiver
- Connect the equipment to an outlet on a different circuit from that to which the receiver is connected
- Consult the dealer or an experienced radio/TV technician for help.

Compliance Accessories: The accessories associated with this equipment are: shielded video cable when an external monitor is connected. These accessories are required to be used in order to ensure compliance with FCC rules.

FCC declaration of conformity

Responsible party:

Gateway Companies, Inc.
610 Gateway Drive, North Sioux City, SD 57049
(605) 232-2000 Fax: (605) 232-2023

Product:

- GTW-P42M102 Plasma TV
- GTW-P42M203 Plasma TV
- GTW-P42M303 Plasma TV

This device complies with Part 15 of the FCC Rules. Operation of this product is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Caution

Changes or modifications not expressly approved by Gateway could void the FCC compliance and negate your authority to operate the product.

Canada

Industry Canada (IC)
Unintentional emitter per ICES-003

This digital apparatus does not exceed the Class B limits for radio noise emissions from digital apparatus as set out in the radio interference regulations of Industry Canada.

Le présent appareil numérique n'émet pas de bruits radioélectriques dépassant les limites applicables aux appareils numériques de Classe B prescrites dans le règlement sur le brouillage radioélectrique édicté par Industrie Canada.

Laser safety statement

All Gateway systems equipped with CD and DVD drives comply with the appropriate safety standards, including IEC 825. The laser devices in these components are classified as "Class 1 Laser Products" under a US Department of Health and Human Services (DHHS) Radiation Performance Standard. Should the unit ever need servicing, contact an authorized service location.

Warning

Use of controls or adjustments or performance of procedures other than those specified in this manual may result in hazardous radiation exposure. To prevent exposure to laser beams, do not try to open the enclosure of a CD or DVD drive.

California Proposition 65 Warning

Warning

This product contains chemicals, including lead, known to the State of California to cause cancer and/or birth defects or reproductive harm.

Television antenna connectors protection (for systems fitted with TV/cable TV tuner cards)

External television antenna grounding

If an outside antenna or cable system is to be connected to your Gateway PC, make sure that the antenna or cable system is electrically grounded to provide some protection against voltage surges and static charges.

Article 810 of the National Electrical Code, ANSI/NFPSA 70, provides information with regard to proper grounding of the mast and supporting structure, grounding of the lead-in wire to an antenna discharge unit, size of grounding conductors, location of antenna discharge unit, connection to grounding electrodes, and requirements for the grounding electrode.

Lightning protection

For added protection of any Gateway product during a lightning storm or when it is left unattended or unused for long periods of time, unplug the product from the wall outlet and disconnect the antenna or cable system.

Power lines

Do not locate the antenna near overhead light or power circuits, or where it could fall into such power lines or circuits.

Warning

When installing or realigning an outside antenna system, extreme care should be taken to keep from touching such power lines or circuits. Contact with them could be fatal.



Antenna and satellite grounding

Reference	Grounding component
1	Electric service equipment
2	Power service grounding electrode system (NEC Art 250, Part H)
3	Ground clamps
4	Grounding conductors (NEC Section 810-21)
5	Antenna discharge unit (NEC Section 810-20)
6	Ground clamp
7	Antenna lead-in wire

Notices

Copyright © 2003 Gateway, Inc.
All Rights Reserved
14303 Gateway Place
Poway, CA 92064 USA

All Rights Reserved

This publication is protected by copyright and all rights are reserved. No part of it may be reproduced or transmitted by any means or in any form, without prior consent in writing from Gateway.

The information in this manual has been carefully checked and is believed to be accurate. However, changes are made periodically. These changes are incorporated in newer publication editions. Gateway may improve and/or change products described in this publication at any time. Due to continuing system improvements, Gateway is not responsible for inaccurate information which may appear in this manual. For the latest product updates, consult the Gateway Web site at www.gateway.com. In no event will Gateway be liable for direct, indirect, special, exemplary, incidental, or consequential damages resulting from any defect or omission in this manual, even if advised of the possibility of such damages.

In the interest of continued product development, Gateway reserves the right to make improvements in this manual and the products it describes at any time, without notices or obligation.

Trademark Acknowledgments

1-800-GATEWAY, ActiveCPR, ALR, AnyKey, black-and-white spot design, CrystalScan, Destination, DestiVu, EZ Pad, EZ Point, Field Mouse, Gateway 2000, Gateway Country, gateway.net, Gateway stylized logo, Perfect Scholar, Solo, TelePath, Vivitron, stylized “G” design, and “You’ve got a friend in the business” slogan are registered trademarks and black-and-white spotted box logo, GATEWAY, Gateway Astro, Gateway@Work, Gateway Connected touch pad, Gateway Connected music player, Gateway Cyber:)Ware, Gateway Education:)Ware, Gateway Flex Case, Gateway Gaming:)Ware, Gateway GoBack, Gateway Gold, Gateway Learning:)Ware, Gateway Magazine, Gateway Micro Server, Gateway Money:)Ware, Gateway Music:)Ware, Gateway Networking Solutions, Gateway Online Network (O.N.) solution, Gateway Photo:)Ware, Gateway Professional PCs, Gateway Profile, Gateway Solo, green stylized GATEWAY, green stylized Gateway logo, Gateway Teacher:)Ware, Gateway Video:)Ware, HelpSpot, InforManager, Just click it!, Learn@Gateway, Kids BackPack, SERVE-TO-ORDER, Server Watchdog, the Spotted G Gateway Logo and the Spotted G Logo, SpotShop, Spotshop.com, and Your:)Ware are trademarks of Gateway, Inc. Intel, Intel Inside logo, and Pentium are registered trademarks and MMX is a trademark of Intel Corporation. Microsoft, MS, MS-DOS, and Windows are trademarks or registered trademarks of Microsoft Corporation. All other product names mentioned herein are used for identification purposes only, and may be the trademarks or registered trademarks of their respective companies.

Index

A

accessories 7
adjust
  brightness 37, 38
  color 37
  contrast 37, 38
  screen width 37, 38
  sound 39
  TV settings 37
Adjustment button 12, 36
amplified speakers
  connecting 28
amplifier
  connecting 29
antenna connection 14
audio and video connection 13, 14
audio in connection 14
audio out connection 14

B

back panel connections 13
batteries 5
brightness 37, 38
burn-in 4, 47

C

cable kits 7
cable TV
  connecting coaxial (RF) 27
channel status 42
cleaning 46
  exterior 46
  screen 46
closed captioning 42
Coaxial (RF) video 18
color 37
component video 18
Component Video 1 connection 14
Component Video 2 connection 14
composite video 18
  connection 14
computer
  connecting 31
  connecting DVI video 31
  connecting RGB video 32
connecting
  amplifier 29
  cable TV 27
  computer 31
  DVD player 19
  external amplified speakers 28
  external monitor 33
  external receiver 29
  HDTV decoder set-top box 22
  off-air TV 27
  power cord 8
  subwoofer 30
  VCR 24
  video camera 24
connections
  antenna 14
  audio and video 13, 14
  audio in 14
  audio out 14
  back panel 13
  Component Video 1 14
  Component Video 2 14
  composite video 14
  DVI 13, 15
  DVI audio in 14
  DVI in 15
  external speaker switch 14
  RGB 13, 15
  RGB audio in 14
  RGB in 15
  RGB out 15
  RS-232 15
  subwoofer 14
  S-Video 14
  Video 1 14

contrast 37, 38

D

DVD player
  connecting component video 19
  connecting composite video 21
  connecting S-Video 20
DVI
  audio in connection 14
  connection 13, 15
  in connection 15

E

external amplified speakers
  connecting 28
external monitor
  connecting 33
external receiver
  connecting 29
external speaker switch connection 14

F

features 2
front panel buttons 11

H

HDTV decoder set-top box
  connecting component video 22
  connecting RGB video 23

I

image burn-in 4, 47
Input button 12

M

main power
  switch 9
  turning on 9
maintenance 45, 46
Menu button 12, 36
monitor
  connecting 33

O

off-air TV
  connecting coaxial (RF) 27
on-screen display
  see OSD
OSD 36
  brightness 37, 38
  channel status 42
  closed captioning 42
  color 37
  contrast 37, 38
  language 43
  other menu 43
  Parental Guide 42
  picture menu 37, 38
  PIP mode 40
  PIP/POP menu 40
  POP mode 41
  screen width 37, 38
  sound menu 39
  timeout 43
  TV menu 42
  zoom 37

P

Parental Guide 42
PIP mode 40
POP mode 41
power
  button 12
  main switch 9
  turning on 9
power cord 5
  connection 8

R

receiver
  connecting 29
remote control 5
remote control sensor 12
Remote control user guide 6
RGB
  audio in connection 14

connection 13, 15
in connection 15
out connection 15
RS-232 connection 15

S

safety 3
screen width 37, 38
Service Center 49
setting up
safety precautions 3
signal frequency
Component 1 and Component 2 52
RGB and DVI 53
TV, AV1, and AV2 52
status LED 12
subwoofer
connecting 30
connection 14
support 49
S-Video 18
connection 14

T

timeout 43
troubleshooting 45, 47

V

VCR
connecting coaxial (RF) 26
connecting composite video 25
connecting S-Video 24
Video 1 connection 14
video camera
connecting composite video 25
connecting S-Video 24
video connections
types of 18
volume button 12

W

wall mount kit 7

Z

zoom 37

MAN MON 42" PLASMA TV GDE R3 7/03

8509357